6 3/4" Aperture *Lytening*® High Wattage Incandescent AirSeal® Insulated Ceiling Frame-In Kit



6 3/4" Aperture: Complete Fixture consists of Reflector Trim & Frame-In Kit. Select each separately.

Frame-In Kit	Reflector Trims — See Individual Reflector Trim Specification Sheets									
	Open Downlight						Adjustable		Enclosed Diffuser	Wall Washer
	Reflector	Satin Cone	Sloped Ceiling	Baffles	Basic White	Cross Blade	Recessed Line Volt.	Recessed Low Volt.		
1104ICX **1104ICXQ*** **1104ICXN** **1104ICXNQ***	**1143** **1144** **1144CD** Cone: **1112†** **1113†** **1113BK†** **1113CD†** **1113WH**	**1108†** **1110†**	**1131** **1131WH** **1131GD** **1131CL** **1131BK** **1133** **1133WH** **1133GD** **1133CL** **1133BK** **1154 Series**	**1105†** **1105WH** **1176** **1176WH** **1179M1** **1179WH** **1117** **1117WH** **1105BNM**	**1170M1** **1171** **1116**	**1132**	**1129†** **1129WH** **1129CL†** **1129CD†** **1129GD†** **1129BK†** Eyeball: **1122** **1122WH** **1123** **1123WH** **1182**	**1155** **1155WH** **1161** **1161WH** **1163** **1164**	**1121** **1124** **1126** **1128** **1134** **1178SH** **1190** Open Wet **1184WH** **1184CD**	**1185** **1186** **1186WH**

†Add NM to catalog number for Natural Metal flange and finish.

*Supplied with integral push-In wire connectors

Features

1. **Housing:** .032" (#20 ga.) aluminum. UL listed for direct contact with thermal insulation. AirSeal® housing minimizes air leak-age to less than 2 CFM at 1.57 PSF (or 75pa), which complies with Model Energy Code (Section 602.3.3) and Washington State Energy Code (Section 502.4) and reduces heat loss and condensation in ceiling. Access door for inspection of junction box.
2. **Mounting Frame:** .032 (22ga.) galvanized steel. Accommodates ceilings up to 1" thick. 3/8" deep integral lip. Locks into position along length of mounting bars with locking screws and bendable slot. Four slots are positioned 90° apart to simplify alignment. Push-in/twist-out roto-clips hold reflector flush to ceiling.
3. **Junction Box:** 2" X 4" X 3 1/2" (22 cu. in.) .032" (#22 ga.) galvanized steel. UL listed for maximum of 6 (#12 ga.) 90°C through branch circuit conductors. Integral cable clamps permit attachment of non-metallic (#12 or #14 ga.) Romex® cable without tools or additional connectors.
4. **Mounting Bars:** .059" (#16 ga.) galvanized steel. Bars pivot for easy attachment and wire-in below ceiling line. Bars extend to accommodate 16" to 24" O.C. joist spacing. Bars can accommodate 12" O.C. joist spacing after a slight field modification (see Instruction Sheet). 1104ICX features integral self tapping phillips screws for secure attachment to wood or metal construction. 1104ICXN features integral nails for secure attachment to wood. Both attach to T-bar ceilings without the need of accessories.
5. **Socket Housing:** Impact extruded aluminum or galvanized steel.
6. **Socket:** Porcelain medium base; nickel plated screw shell. Pre-wired with #18 ga. SF1 (300 Volt 200° C) leads to junction box.
7. **Thermal Protector:** Meets NEC and UL requirements. DIMM. Located inside housing.

Options & Accessories

Extra-Thick Ceiling Mounting Ring: **1967A -** up to 2" thick ceilings

Labels

UL (Type I.C., Suitable for Damp Location), I.B.E.W.

Complies with Air Leakage Requirements stated in the Model Energy Code, California Title 24 and the Washington State Energy Code.

AirSeal® is a registered trademark of Lightolier.
Romex® is a registered trademark of General Cable Industries Inc.-
US and Foreign Patents Pending.

Job Information **Type:**

Job Name:

Cat. No.:

Lamp(s):

Notes:

Lightolier a Genlyte company www.lightolier.com
631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710
We reserve the right to change details of design, materials and finish.
© 2007 Genlyte Group LLC • I0807

LIGHTOLIER®